

MODEL		EXTREME 9
	Units	Cooling
Cooling (35°C d.b.; 80% r.h.)	BTU/h	9 000
Rated Cooling capacity (35°C/24° C)	kW	2,4
Energy label class		A
Rated EER - COP	(kW/kW)	2,8
Air flowrate (l.-m.-h.)	m ³ h	400-380-350
Dehumidification	l/24h	40
Fan speeds	n.	3 + auto
Sound pressure (l.-m.-h.)	dB(A)	35-36-38
Sound power (h.)	dB(A)	60
Power supply	V/Ph/Hz	230/1/50
Rated Power input	kW	0,870
Hourly electricity consumption	kWh/60 min	0,9
Thermostat-off mode power consumption	W	148
Standby mode power consumption	W	< 0,5
Refrigerant type		R410A
Refrigerant GWP	kgCO ₂ eq.	1975
Hole in the window (diameter)	mm	140
Flexible exhaust tube (diameter)	mm	135
Flexible exhaust tube (extended lenght)	m	1,2
Net weight	Kg	26,5
Net dimension (H./W./D.)	mm	725x505x310

Data declared in compliance with EU Regulation no. 206/2012, as regards to ECO-design requirements for air conditioners and comfort fans, and EU Regulation no. 626/2011, concerning the energy labelling of air conditioners.